

## Projektor

<b>Projector Minimum Requirements:</b>
<i>Model</i>
<i>Ansi Lumen :</i>
<i>Resolution :</i>
<i>Input signals :</i>
<i>Input terminals</i>
<i>Output terminals :</i>
<i>Interface :</i>
<i>Horizontal frequency :</i>
<i>Vertical frequency :</i>
<i>Lamp life :</i>
<i>Contrast ratio :</i>
<i>Lens :</i>
<i>Accessories :</i>
Warranty

Projektor Standard
DTV/HDTV Compatible
2300
Min 1024 x 768
DTV, NTSC,PAL, Computer RGB
DVI-D (Compatible with HDCP) , Computer Component , S-Video, Video (RCA), Audio stereo , Audio (RCA) (L/R)
Computer / Component , Audio stereo
USB , RS-232C
15 - 70 kHz
45 - 85 Hz
3,500 hours
2,000:1
F number, Zoom manual, Focus manual
Remote control, power cord , RGB cable , lens cap, operation manual, CD-ROM, PC-Mouse control (via USB) , carrying case
2 vjet

<b>Skaner</b>
---------------

<b>Scanner Minimum Requirements:</b>
<i>type</i>
<i>max size</i>
<i>grayscale depth</i>
<i>color depth</i>
<i>optical resolution</i>
<i>scan mode</i>
<i>media feeder type</i>
<i>interfaces</i>
<i>power</i>
<i>software</i>
<i>warranty</i>

<b>Scanner Type 1</b>
flatbed
A4
16
48
1200x4800
single pass
manual
usb
240 V
Drivers
1 years

<b>Scanner Type 2</b>
flatbed
A4
16
48
4800x9600
single pass
manual/authomatic with ADF
usb
240V
at least OCR
3 years

**UPS**

<b>UPS Minimum Requirements</b>
<i>Power :</i>
<i>Input voltage :</i>
<i>Input voltage window :</i>
<i>Output voltage</i>
<i>Voltage regulation (On battery) :</i>
<i>Output frequency :</i>
<i>Transfer time :</i>
<i>Protection :</i>
<i>Back-Up time :</i>
<i>AVR :</i>
<i>Outlets:</i>
<i>Shutdown Software :</i>
<i>Standard Warranty</i>

<b>UPS Type</b>
1000VA
220/230/240 VAC
170 – 270 VAC
220/230/240 VAC
+/-10%
50 Hz
jo me shume se 4ms
Discharge, overcharge
Min. 5 min full load
YES
3 outlets IEC 320 C13 + 1 surge outlets IEC 320 C13, 2 RJ11 connectors for fax / modem protection ,telephone cable provided
YES
2 vjet